

GreenFlex Superclean W



GreenFlex Superclean W is a safe, powerful, and biodegradable product for the removal of waterborne paint, coatings and inks

- High flash point and does not require separate storage
- Biodegradable
- Water-dilutable
- No hazard labels
- Non-foaming
- Residue-free
- Safe for use on various materials, including plastics and metals
- Free from volatile organic hydrocarbons (VOS), methylene chloride, and N-Methyl-2-pyrrolidone (NMP)
- Fast and oil-free drying of cleaned object
- Non-alkaline
- Effective on dried waterborne paint, coatings and inks

APPLICATION

GreenFlex Superclean W is an effective cleaning agent specifically developed for waterborne paint, coatings and inks. Applicable on rolls, rubber clichés, rotogravure cylinders, doctor blades, floors and walls, spray booths, tools, and printing equipment.

PROPERTIES

Density (20°C)	: 1,03 kg/l
Colour	: clear
Flash point (closed cup)	: 85 °C
Odour	: mild

INSTRUCTIONS FOR USE

GreenFlex Superclean W can be sprayed, immersed, and brushed, or applied with a cloth. For stubborn stains, immerse objects in GreenFlex Superclean W. Absorption time may vary from 1 to 45 minutes, depending on the stain. Rinse thoroughly with water. The solution can be diluted with a maximum of 1 part product to 5 parts water. The diluted product has a maximum shelf life of 1 month.

HAZARDS & PRECAUTIONARY STATEMENTS

Hazards and precautionary statements: see our Material Safety Data Sheet.

VECOM Specialists in Maintenance & Surface Treatment

Our product details are obligation-free. Since their application lies outside our control, we cannot accept liability for the results. For contact details visit: www.vecom-group.com

www.vecom-group.com